



Separate Drive Rotary Vane 55 cfm



Lubricated 5565 Series



MODEL 5565 SERIES

25" HG MAX. VAC., 55 CFM OPEN FLOW

PRODUCT FEATURES

- Lubricated operation
- Rugged construction/low maintenance
- Essentially pulse-free service

INCLUDES


- Filter AD560
- Muffler AD560B
- Oil reservoir AD185
- Motorized lubricator AD190-V4
- Coupling AE544B-1 (.88" x 1.13")

RECOMMENDED ACCESSORIES

- Base AB322E
- Vacuum relief valve AE961
- Vacuum gauge AA640
- Oil AD220
- Repair kit K299
- Coupling guard AH380B-1

Product Dimensions (mm, inches)

Dimensions are for reference only.



Product Specifications

Model Number	Motor	Base	Coupling Guard	RPM		HP	kW	Net Wt.	
				60 Hz	50 Hz			lbs.	kg
5565-V4	—			1725	—	3	2,2	95	42,8
5565-V5A	—	•	•	1725	—	3	2,2	140	63,0
5565-V7	—			1725	—	3	2,2	95	42,8
5565-V6A-T338	230/460-60-3	•	•	1725	—	3	2,2	172	77,4
5565-V7-SD220-1*	415-50-3	•	•	—	1425	3	2,2	172	77,4

*Available only in Europe.

Product Performance (Metric, U.S.)

